

Revision date: 11.12.2020

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

PEC-III, Comp. A

Page 1 of 13

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

PEC-III, Comp. A

UFI:

KTPV-203E-V008-QRWP

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Adhesive mortar for fastening elements A-component (resin)

#### Uses advised against

no restriction

### 1.3. Details of the supplier of the safety data sheet

Company name:	UIP Verbindungstechnik GmbH	
Street:	Kapellenstraße 47	
Place:	D-65830 Kriftel	
Telephone:	+49 6192 9578050	Telefax:+49 6192 9578055
e-mail:	office@uip-systems.com	
Internet:	www.uip-systems.com	
1.4. Emergency telephone	+49 (0)551-19240 (GIZ-Nord, Ger	man and English, 24/7)
<u>number:</u>		

# SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

### Regulation (EC) No. 1272/2008

Hazard categories: Skin corrosion/irritation: Skin Irrit. 2 Serious eye damage/eye irritation: Eye Irrit. 2 Respiratory or skin sensitisation: Skin Sens. 1 Hazardous to the aquatic environment: Aquatic Chronic 2 Hazard Statements: Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. Toxic to aquatic life with long lasting effects.

### 2.2. Label elements

### Regulation (EC) No. 1272/2008

#### Hazard components for labelling

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane; Bisphenol-F-epichlorohydrin resin MM <= 700; 1,6-Bis(2,3-epoxypropoxy)hexane Signal word: Warning

Signal word

Pictograms:



#### Hazard statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.



according to Regulation (EC) No 1907/2006

# PEC-III, Comp. A

Revision date: 11.12.2020

Page 2 of 13

#### **Precautionary statements**

P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P391	Collect spillage.

#### Special labelling of certain mixtures

EUH205 Contains epoxy constituents. May produce an allergic reaction.

### 2.3. Other hazards

People who are allergic to epoxide should avoid the use of the product. Use only outdoors or in a well-ventilated area.

#### **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

#### Hazardous components

CAS No	Chemical name		Quantity	
	EC No	Index No	REACH No	
	GHS Classification			
1675-54-3	2,2'-[(1-methylethylidene)bis(4,7	I-phenyleneoxymethylene)]bisox	irane	25 - < 50 %
	216-823-5	603-073-00-2	01-2119456619-26	
	Skin Irrit. 2, Eye Irrit. 2, Skin Se	ns. 1, Aquatic Chronic 2; H315 H	I319 H317 H411	
9003-36-5	Bisphenol-F-epichlorohydrin res		10 - < 20 %	
	500-006-8		01-2119454392-40	
	Skin Irrit. 2, Skin Sens. 1, Aqua	tic Chronic 2; H315 H317 H411		
933999-84-9	1,6-Bis(2,3-epoxypropoxy)hexa	ne		10 - < 20 %
	618-939-5		01-2119463471-41	
	Skin Irrit. 2, Eye Irrit. 2, Skin Se	I319 H317 H412		
	Alkyl Ester (Ref.: 722 43/00/201		1 - 10 %	
	Eye Irrit. 2; H319			

Full text of H and EUH statements: see section 16.

#### Specific concentration limits and M-factors

CAS No	EC No	Chemical name	Quantity
	Specific conce	entration limits and M-factors	
1675-54-3	216-823-5	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	25 - < 50 %
	Skin Irrit. 2; H3	315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100	

#### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

#### **General information**

First aider: Pay attention to self-protection! Take off immediately all contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.

#### After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

#### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated



according to Regulation (EC) No 1907/2006

# PEC-III, Comp. A

Revision date: 11.12.2020

Page 3 of 13

clothing and wash it before reuse. Medical treatment necessary.

#### After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

#### After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Medical treatment necessary.

#### 4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### Suitable extinguishing media

Foam Extinguishing powder Water spray jet Carbon dioxide (CO2)

### Unsuitable extinguishing media

Full water jet

#### 5.2. Special hazards arising from the substance or mixture

Pyrolysis products, toxic Carbon monoxide

#### 5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit

#### Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Provide adequate ventilation.

#### 6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter into surface water or drains.

#### 6.3. Methods and material for containment and cleaning up

Collect spillage. Take up mechanically, placing in appropriate containers for disposal. Suitable material for taking up: Sand

Treat the recovered material as prescribed in the section on waste disposal.

Retain contaminated washing water and dispose it.

### 6.4. Reference to other sections

### Safe handling: see section 7

Personal protection equipment: see section 8 Disposal: see section 13

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling



according to Regulation (EC) No 1907/2006

# PEC-III, Comp. A

Revision date: 11.12.2020

Advice on safe handling

Use only outdoors or in a well-ventilated area. Wear personal protection equipment (refer to section 8). Avoid contact with skin, eyes and clothes. When using do not eat, drink or smoke.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed. Store in a place accessible by authorized persons only. Keep only in the original container in a cool, well-ventilated place.

### Hints on joint storage

Do not store together with: Oxidising agent, strong Do not use for products which come into contact with the food stuffs.

#### Further information on storage conditions

storage temperature: 5 - 35°C

# 7.3. Specific end use(s)

Adhesive mortar for fastening elements A-component (resin)

#### SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Page 4 of 13



according to Regulation (EC) No 1907/2006

# PEC-III, Comp. A

Page 5 of 13

# Revision date: 11.12.2020

# DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
9003-36-5	Bisphenol-F-epichlorohydrin resin MM <= 700			
Worker DNEI	L, acute	dermal	local	0,0083 mg/cm <sup>2</sup>
Worker DNEI	L, long-term	dermal	systemic	104,15 mg/kg bw/day
Worker DNEI	L, long-term	inhalation	systemic	29,39 mg/m <sup>3</sup>
Consumer DI	NEL, long-term	dermal	systemic	62,5 mg/kg bw/day
Consumer DI	NEL, long-term	inhalation	systemic	8,7 mg/m³
Consumer DI	NEL, long-term	oral	systemic	6,25 mg/kg bw/day
933999-84-9	1,6-Bis(2,3-epoxypropoxy)hexane			
Worker DNEI	L, long-term	inhalation	systemic	10,57 mg/m <sup>3</sup>
Worker DNEI	L, long-term	inhalation	local	0,44 mg/m <sup>3</sup>
Worker DNEI	L, long-term	dermal	systemic	6,0 mg/kg bw/day
Worker DNEI	L, long-term	dermal	local	0,0226 mg/cm <sup>2</sup>
Consumer DI	NEL, long-term	inhalation	systemic	5,29 mg/m <sup>3</sup>
Consumer DI	NEL, long-term	inhalation	local	0,27 mg/m³
Consumer DI	NEL, long-term	dermal	systemic	3,0 mg/kg bw/day
Consumer DI	NEL, long-term	dermal	local	0,0136 mg/cm <sup>2</sup>
Consumer DI	NEL, acute	inhalation	systemic	5,29 mg/m <sup>3</sup>
Consumer DI	NEL, acute	dermal	systemic	1,7 mg/kg bw/day
Consumer DI	NEL, acute	dermal	local	0,0136 mg/cm <sup>2</sup>
Consumer DI	NEL, long-term	oral	systemic	1,5 mg/kg bw/day
Consumer DI	NEL, acute	oral	systemic	1,5 mg/kg bw/day
PNEC value	es			
CAS No	Substance			
Environmenta	al compartment			Value
9003-36-5	Bisphenol-F-epichlorohydrin resin MM <= 700			
Freshwater				0,003 mg/l
Marine water				0,0003 mg/l
Freshwater s	ediment			0,294 mg/kg
Marine sedim	nent			0,0294 mg/kg
Secondary po	pisoning			0,0254 mg/l
Micro-organis	10 mg/l			
Soil				0,237 mg/kg
933999-84-9	1,6-Bis(2,3-epoxypropoxy)hexane			
Freshwater				0,0115 mg/l
Marine water				0,00115 mg/l
Freshwater se	ediment			0,283 mg/kg
Marine sedim				0,283 mg/kg



according to Regulation (EC) No 1907/2006

# PEC-III, Comp. A

Page 6 of 13

#### Revision date: 11.12.2020

### Additional advice on limit values

This mixture contains quartz filler which is firmly bound in the pasty component, and thus not freely available during use, so that a risk of dust inhalation is excluded. Exposure limit values for respirable dusts are not relevant for this product.

### 8.2. Exposure controls







#### Appropriate engineering controls

Provide adequate ventilation. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

#### Protective and hygiene measures

Take off contaminated clothing and wash it before reuse. Draw up and observe skin protection programme. Wash hands thoroughly after handling. When using do not eat, drink or smoke.

#### Eye/face protection

Wear eye protection/face protection. Wear safety glasses.

#### Hand protection

Recommended material: NBR (Nitrile rubber) Breakthrough time: > 480 min Thickness of the glove material: 0,7 mm DIN-/EN-Norms: EN 374

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

#### Skin protection

Wear suitable protective clothing.

#### **Respiratory protection**

In case of inadequate ventilation wear respiratory protection. Respiratory protection with combination filter A1P2 (organic gases/vapors and particles) recommended.

### **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state: Colour: Odour: Odour threshold:	solid (pasty) light beige characteristic No data available	
pH-Value:		not determined
Changes in the physical state		
Melting point:		not determined
Initial boiling point and boiling range:		not determined
Flash point:		not applicable
Flammability		
Solid:		not determined
Gas:		not applicable
Lower explosion limits:		not determined
Upper explosion limits:		not determined



according to Regulation (EC) No 1907/2006

# PEC-III, Comp. A

Page 7 of 13

Auto-ignition temperature		
Solid:	not determined	
Gas:	not applicable not determined	
Decomposition temperature:	not determined	
Oxidizing properties Not oxidising.		
Vapour pressure:	not determined	
Density (at 20 °C):	1,49 g/cm <sup>3</sup>	
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.	
Solubility in other solvents not determined		
Partition coefficient:	not determined	
Vapour density:	not determined	
Evaporation rate:	not determined	
9.2. Other information		
Solid content:	not determined	
SECTION 10: Stability and reactivity		
10.1. Reactivity		_
10.1. Reactivity No hazardous reaction when handle	ed and stored according to provisions.	
<u>10.1. Reactivity</u> No hazardous reaction when handle <u>10.2. Chemical stability</u>	ed and stored according to provisions.	
<u>10.1. Reactivity</u> No hazardous reaction when handle <u>10.2. Chemical stability</u> The product is stable under storage	ed and stored according to provisions. at normal ambient temperatures.	
<u>10.1. Reactivity</u> No hazardous reaction when handle <u>10.2. Chemical stability</u> The product is stable under storage <u>10.3. Possibility of hazardous reactions</u>	ed and stored according to provisions. at normal ambient temperatures.	
<u>10.1. Reactivity</u> No hazardous reaction when handle <u>10.2. Chemical stability</u> The product is stable under storage <u>10.3. Possibility of hazardous reactions</u> Violent reaction with: Oxidising agen	ed and stored according to provisions. at normal ambient temperatures.	
<u>10.1. Reactivity</u> No hazardous reaction when handle <u>10.2. Chemical stability</u> The product is stable under storage <u>10.3. Possibility of hazardous reactions</u>	ed and stored according to provisions. at normal ambient temperatures. t, strong	
10.1. Reactivity   No hazardous reaction when handle   10.2. Chemical stability   The product is stable under storage   10.3. Possibility of hazardous reactions   Violent reaction with: Oxidising agen   10.4. Conditions to avoid   Heat. Keep cool. Protect from sunlig   10.5. Incompatible materials	ed and stored according to provisions. at normal ambient temperatures. t, strong	
10.1. Reactivity   No hazardous reaction when handle   10.2. Chemical stability   The product is stable under storage   10.3. Possibility of hazardous reactions   Violent reaction with: Oxidising agen   10.4. Conditions to avoid   Heat. Keep cool. Protect from sunlig   10.5. Incompatible materials   Keep away from: Oxidizing agent	ed and stored according to provisions. at normal ambient temperatures. t, strong ht.	
10.1. Reactivity   No hazardous reaction when handled   10.2. Chemical stability   The product is stable under storage   10.3. Possibility of hazardous reactions   Violent reaction with: Oxidising agen   10.4. Conditions to avoid   Heat. Keep cool. Protect from sunlig   10.5. Incompatible materials   Keep away from: Oxidizing agent   10.6. Hazardous decomposition product	ed and stored according to provisions. at normal ambient temperatures. It, strong ht.	
10.1. Reactivity   No hazardous reaction when handle   10.2. Chemical stability   The product is stable under storage   10.3. Possibility of hazardous reactions   Violent reaction with: Oxidising agen   10.4. Conditions to avoid   Heat. Keep cool. Protect from sunlig   10.5. Incompatible materials   Keep away from: Oxidizing agent	ed and stored according to provisions. at normal ambient temperatures. It, strong ht.	
10.1. Reactivity   No hazardous reaction when handled   10.2. Chemical stability   The product is stable under storage   10.3. Possibility of hazardous reactions   Violent reaction with: Oxidising agen   10.4. Conditions to avoid   Heat. Keep cool. Protect from sunlig   10.5. Incompatible materials   Keep away from: Oxidizing agent	ed and stored according to provisions. at normal ambient temperatures. t, strong ht. <b>ts</b> products.	
10.1. Reactivity   No hazardous reaction when handled   10.2. Chemical stability   The product is stable under storage   10.3. Possibility of hazardous reactions   Violent reaction with: Oxidising agen   10.4. Conditions to avoid   Heat. Keep cool. Protect from sunlig   10.5. Incompatible materials   Keep away from: Oxidizing agent   10.6. Hazardous decomposition product   No known hazardous decomposition	ed and stored according to provisions. at normal ambient temperatures. t, strong ht. <b>ts</b> products. <b>ion</b>	



Page 8 of 13

### according to Regulation (EC) No 1907/2006

# PEC-III, Comp. A

Revision date: 11.12.2020

CAS No	Chemical name								
	Exposure route	Dose		Species	Source	Method			
9003-36-5	Bisphenol-F-epichloroh	Bisphenol-F-epichlorohydrin resin MM <= 700							
		LD50 mg/kg	> 2000	Rat					
		LD50 mg/kg	> 2000	Rat					
933999-84-9	1,6-Bis(2,3-epoxypropo	xy)hexane							
		LD50 mg/kg	2190	Rat		OECD 401			
		LD50 mg/kg	> 2000	Rat		OECD 402			
	inhalation (4 h) vapour	LC50 mg/l	0,035	Rat					
	Alkyl Ester (Ref.: 722 4	3/00/2012.0	)028, Gern	nany)					
	• • •••	LD50 mg/kg	20700	Mouse					
		LD50 mg/kg	2000	Rabbit					

### Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

### Sensitising effects

Contains epoxy constituents. May produce an allergic reaction.May cause an allergic skin reaction. (2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane; Bisphenol-F-epichlorohydrin resin MM <= 700; 1,6-Bis(2,3-epoxypropoxy)hexane)

# Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

# Aspiration hazard

Based on available data, the classification criteria are not met.

#### Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

### **SECTION 12: Ecological information**

### 12.1. Toxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.



Page 9 of 13

### according to Regulation (EC) No 1907/2006

# PEC-III, Comp. A

Revision date: 11.12.2020

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method
9003-36-5	Bisphenol-F-epichlorohy	/drin resin l	MM <= 700	)			
	Acute fish toxicity	LC50 mg/l	2,54		Brachydanio rerio (zebra-fish)		
	Acute algae toxicity	ErC50	1,8 mg/l		Selenastrum capricornutum		
	Acute crustacea toxicity	EC50 mg/l	2,55		Daphnia magna (Big water flea)		
933999-84-9	1,6-Bis(2,3-epoxypropo	ky)hexane					
	Acute fish toxicity	LC50	30 mg/l		Oncorhynchus mykiss (Rainbow trout)		
	Acute crustacea toxicity	EC50	47 mg/l		Daphnia magna (Big water flea)		

# 12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
9003-36-5	Bisphenol-F-epichlorohydrin resin MM <= 700			
	OECD 301B	16 %	28	
933999-84-9	1,6-Bis(2,3-epoxypropoxy)hexane			
	OECD 301D	71 %	28	

#### 12.3. Bioaccumulative potential

The product has not been tested.

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
9003-36-5	Bisphenol-F-epichlorohydrin resin MM <= 700	3,3
933999-84-9	1,6-Bis(2,3-epoxypropoxy)hexane	0,822

BCF

CAS No Chemical name		BCF	Species	Source
933999-84-9	1,6-Bis(2,3-epoxypropoxy)hexane	3,57		

### 12.4. Mobility in soil

The product has not been tested.

### 12.5. Results of PBT and vPvB assessment

The product has not been tested.

#### 12.6. Other adverse effects

No information available.

#### Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

#### **Disposal recommendations**

Subsequent waste code numbers of the European Waste Catalogue are considered as recommendations. Dispose of waste according to applicable legislation. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.



according to Regulation (EC) No 1907/2006

# PEC-III, Comp. A

Revision date: 11.12.2020

Page 10 of 13

#### List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

### List of Wastes Code - used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

#### List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

#### **SECTION 14: Transport information**

#### Land transport (ADR/RID)

<u>14.1. UN number:</u>	UN 3077
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Epoxy resin)
14.3. Transport hazard class(es):	9
14.4. Packing group:	III
Hazard label:	9
Classification code:	M7
Special Provisions:	274 335 375 601
Limited quantity:	5 kg
Excepted quantity:	E1
Transport category:	3
Hazard No:	90
Tunnel restriction code:	-
Other applicable information (land to No dangerous goods in packaging	r <b>ansport)</b> until 5 kg according special instruction 375 ADR/RID
Inland waterways transport (ADN)	
<u>14.1. UN number:</u>	UN 3077
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Epoxy resin)
14.3. Transport hazard class(es):	9
14.4. Packing group:	III
Hazard label:	9
Classification code:	M7



according to Regulation (EC) No 1907/2006

# PEC-III, Comp. A

Revision date: 11.12.2020	Page 11 of 13
Special Provisions:	274 335 375 601
Limited quantity:	5 kg E1
Excepted quantity: Other applicable information (inland	
	until 5kg according special instruction 375 ADN
Marine transport (IMDG)	
<u>14.1. UN number:</u>	UN 3077
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Epoxy resin)
14.3. Transport hazard class(es):	9
14.4. Packing group:	
Hazard label:	9
	9
Special Provisions:	274, 335, 966, 967, 969
Limited quantity:	5 kg
Excepted quantity: EmS:	E1 F-A, S-F
Other applicable information (marine	
	until 5kg according 2.10.2.7 IMDG-Code
Air transport (ICAO-TI/IATA-DGR)	
<u>14.1. UN number:</u>	UN 3077
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Epoxy resin)
14.3. Transport hazard class(es):	9
14.4. Packing group:	III
Hazard label:	9
	e
Special Provisions:	A97 A158 A179 A197
Limited quantity Passenger:	30 kg G
Passenger LQ:	Y956 E1
Excepted quantity:	
IATA-packing instructions - Passenger: IATA-max. quantity - Passenger:	956 400 kg
IATA-packing instructions - Cargo:	956
IATA-max. quantity - Cargo:	400 kg
Other applicable information (air train No dangerous goods in packaging to the second	
14.5. Environmental hazards	
ENVIRONMENTALLY HAZARDOUS:	yes



No information available.



according to Regulation (EC) No 1907/2006

### PEC-III, Comp. A

Page 12 of 13

#### Revision date: 11.12.2020

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

### **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulatory information

Information according to 2012/18/EU E2 Hazardous to the Aquatic Environment (SEVESO III):

#### Additional information

VOC content: 0,9 % (DIN EN ISO 11890-2)

To follow: 850/2004/EC , 79/117/EEC , 689/2008/EC

#### National regulatory information

Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile
	work protection guideline' (94/33/EC).
Water hazard class (D):	2 - obviously hazardous to water
Skin resorption/Sensitization:	Causes allergic hypersensitivity reactions.

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### **SECTION 16: Other information**

#### Abbreviations and acronyms

ADN: Accord européen relativ au transport international des marchandises Dangereuses par voie de Navigation (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways) ADR: Accord européen sur le transport des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) CAS: Chemical Abstracts Service CLP: Classification, Labeling and Packaging DMEL: Derived Minimal Effect level **DNEL: Derived No Effect Level** EC50: Effective concentration, 50% IATA: International Air Transport Association IATA-DGR: Dangerous Goods Regulations (DRG) for the air transport (IATA) IMDG: International Maritime Dangerous Goods Code LC50: Lethal concentration, 50% LD50: Lethal dose, 50% NOEC: No Observed Effect Concentration OECD: Oragnisation for Economic Co-operation and Development PBT: persistent, bioaccumulative and toxic vPvB: very persistent and very bioaccumulative PNEC: Predicted No Effect Concentration REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals RID: Règlement concernant le transport international ferroviaire des marchandises dangereuses (Regulations Concerning the International Carriage of Dangerous Goods by Rail) VOC: Volatile organic compound Aquatic Chronic 2: Long-term aquatic hazard, Category 2 Aquatic Chronic 3: Long-term aquatic hazard, Category 3 Eye Irrit. 2: Serious eye damage/eye irritation, Category 2 Skin Irrit. 2: Serious eve damage/eve irritation, Category 2 Skin Sens. 1: Skin sensitilization, Category 1



according to Regulation (EC) No 1907/2006

# PEC-III, Comp. A

Revision date: 11.12.2020

Page 13 of 13

# Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 2; H411	Calculation method

### Relevant H and EUH statements (number and full text)

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
<b>E</b> 111100E	

EUH205 Contains epoxy constituents. May produce an allergic reaction.

### **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)



Revision date: 11.12.2020

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

PEC-III, Comp. B

Page 1 of 16

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

PEC-III, Comp. B

UFI:

YWPV-J0SU-500S-C3GR

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

compound mortar B-component (hardener)

#### Uses advised against

no restriction

#### 1.3. Details of the supplier of the safety data sheet

Company name:	UIP Verbindungstechnik GmbH	
Street:	Kapellenstraße 47	
Place:	D-65830 Kriftel	
Telephone:	+49 6192 9578050	Telefax:+49 6192 9578055
e-mail:	office@uip-systems.com	
Internet:	www.uip-systems.com	
1.4. Emergency telephone	+49 (0)551-19240 (GIZ-Nord, Gern	nan and English, 24/7)
<u>number:</u>		

### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

#### Regulation (EC) No. 1272/2008

Hazard categories: Acute toxicity: Acute Tox. 4 Skin corrosion/irritation: Skin Corr. 1B Serious eve damage/eve irritation: Eve Dam. 1 Respiratory or skin sensitisation: Skin Sens. 1 Germ cell mutagenicity: Muta. 2 Reproductive toxicity: Repr. 1B Hazardous to the aquatic environment: Aquatic Chronic 3 Hazard Statements: Harmful if swallowed. Causes severe skin burns and eye damage. Causes serious eye damage. May cause an allergic skin reaction. Suspected of causing genetic defects. May damage fertility. Harmful to aquatic life with long lasting effects.

### 2.2. Label elements

### Regulation (EC) No. 1272/2008

#### Hazard components for labelling

3-aminomethyl-3,5,5-trimethylcyclohexylamine; Formaldehyde, oligomeric reaction products with phenol and m-phenylenebis(methylamine); m-Phenylenebis(methylamine); Formaldehyde, oligomeric reaction products with 4,4´-isopropylidenediphenol and diethylenetriamine; Diethylenetriamine; Phenol; Bisphenol A Signal word: Danger

Revision No: 2,18



according to Regulation (EC) No 1907/2006

# PEC-III, Comp. B

Revision date: 11.12.2020

**Pictograms:** 

Page 2 of 16



# Hazard statements

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H341	Suspected of causing genetic defects.
H360F	May damage fertility.
H412	Harmful to aquatic life with long lasting effects.

#### **Precautionary statements**

Obtain special instructions before use.
Avoid release to the environment.
Wear protective gloves/protective clothing/eye protection/face protection.
IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
Immediately call a POISON CENTER/doctor.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

#### 2.3. Other hazards

Contains Amines. May produce an allergic reaction.

Use only outdoors or in a well-ventilated area.

# **SECTION 3: Composition/information on ingredients**

### 3.2. Mixtures



according to Regulation (EC) No 1907/2006

# PEC-III, Comp. B

Revision date: 11.12.2020

Page 3 of 16

# Hazardous components

CAS No	Chemical name			Quantity	
	EC No	Index No	REACH No		
	GHS Classification				
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine				
	220-666-8	612-067-00-9	01-2119514687-32		
	Acute Tox. 4, Acute Tox. 4, S H302 H314 H318 H317 H41	kin Corr. 1B, Eye Dam. 1, 2	Skin Sens. 1, Aquatic Chronic 3; H312		
1950616-36-0	Formaldehyde, oligomeric re	eaction products with pheno	I and m-phenylenebis(methylamine)	15 - < 25 %	
	701-207-5		01-2119966906-20		
	Skin Corr. 1C, Eye Dam. 1,	Skin Sens. 1B, Aquatic Chr	onic 3; H314 H318 H317 H412		
1477-55-0	m-Phenylenebis(methylamin	ie)		15 - < 25 %	
	216-032-5		01-2119480150-50		
	Acute Tox. 4, Acute Tox. 4, S H302 H314 H318 H317 H41		Skin Sens. 1B, Aquatic Chronic 3; H332		
77138-45-5	Formaldehyde, oligomeric re diethylenetriamine	eaction products with 4,4'-is	opropylidenediphenol and	< 10,5 %	
	500-263-6		01-2120769506-44		
	Repr. 2, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1, STOT SE 3; H361f H314 H318 H317 H335				
90-72-2	2,4,6-Tris(dimethylaminomethyl)phenol				
	202-013-9		01-2119560597-27		
	Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2; H302 H315 H319				
100-51-6	Benzyl alcohol				
	202-859-9	603-057-00-5	01-2119492630-38		
	Acute Tox. 4, Acute Tox. 4, Eye Irrit. 2; H332 H302 H319				
111-40-0	Diethylenetriamine			< 7 %	
	203-865-4	612-058-00-X	01-2119473793-27		
	Acute Tox. 2, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Skin Sens. 1, STOT SE 3; H330 H312 H302 H314 H317 H335				
108-95-2	Phenol			1 - < 5 %	
	203-632-7	604-001-00-2	01-2119471329-32		
	Muta. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, Skin Corr. 1B, Eye Dam. 1, STOT RE 2, Aquatic Chronic 2; H341 H331 H311 H301 H314 H318 H373 H411				
71074-89-0	Bis[(dimethylamino)methyl]p	henol		1 - < 5 %	
	275-162-0				
	Skin Corr. 1B, Eye Dam. 1; H314 H318				
80-05-7	Bisphenol A				
	201-245-8	604-030-00-0	01-2119457856-23		
	Repr. 1B, Eye Dam. 1, Skin Sens. 1, STOT SE 3, Aquatic Chronic 2; H360F H318 H317 H335 H411				

Specific concentration limits and M-factors

CAS No	EC No	C No Chemical name	
	Specific conce	Specific concentration limits and M-factors	
108-95-2	203-632-7	Phenol	1 - < 5 %
	Skin Corr. 1B;	H314: >= 3 - 100 Skin Irrit. 2; H315: >= 1 - < 3 Eye Irrit. 2; H319: >= 1 - < 3	



according to Regulation (EC) No 1907/2006

# PEC-III, Comp. B

Revision date: 11.12.2020

Page 4 of 16

### **Further Information**

SVHC list (Candidate List of Substances of Very High Concern for authorization): The product contains one of the listed substances: Bisphenol A

This mixture is place on the market in a form in which aerosol formation cannot occur during intended use and may only be used for applications in which aerosol formation is excluded. Workplace measurements to determine the exposure of users towards contained hazardous substances were carried out. Test reports show no need for the classification of the product as toxic by inhalation. The test reports are available. According to Article 6 of Regulation EC No. 1272/2008, classification and labeling as inhalation toxic is therefore not required.

### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### General information

First aider: Pay attention to self-protection! Remove affected person from the danger area and lay down. Take off immediately all contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.

#### After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

#### After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

#### After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Medical treatment necessary.

#### 4.2. Most important symptoms and effects, both acute and delayed

Harmful if swallowed. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Suspected of causing genetic defects. May damage fertility.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

#### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### Suitable extinguishing media

Foam Extinguishing powder Water spray jet Carbon dioxide (CO2)

#### Unsuitable extinguishing media

Full water jet

#### 5.2. Special hazards arising from the substance or mixture

Pyrolysis products, toxic Carbon monoxide

# 5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.



according to Regulation (EC) No 1907/2006

# PEC-III, Comp. B

Page 5 of 16

Revision date: 11.12.2020

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit

#### Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Provide adequate ventilation.

#### 6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter into surface water or drains.

#### 6.3. Methods and material for containment and cleaning up

Collect spillage. Take up mechanically, placing in appropriate containers for disposal. Suitable material for taking up: Sand

Treat the recovered material as prescribed in the section on waste disposal.

Retain contaminated washing water and dispose it.

# 6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

#### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

#### Advice on safe handling

Use only outdoors or in a well-ventilated area. Wear personal protection equipment (refer to section 8). Avoid contact with skin, eyes and clothes. When using do not eat, drink or smoke.

#### 7.2. Conditions for safe storage, including any incompatibilities

#### **Requirements for storage rooms and vessels**

Keep container tightly closed. Store in a place accessible by authorized persons only. Keep only in the original container in a cool, well-ventilated place.

#### Hints on joint storage

Do not store together with: Oxidising agent, strong, Organic peroxides Do not use for products which come into contact with the food stuffs.

#### Further information on storage conditions

Keep container tightly closed in a cool place. storage temperature: 5 - 35°C

# 7.3. Specific end use(s)

see section 1.2

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters



according to Regulation (EC) No 1907/2006

# PEC-III, Comp. B

Page 6 of 16

Revision date: 11.12.2020

# Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
111-40-0	2,2'-Iminodi(ethylamine)	1	4.3		TWA (8 h)	WEL
80-05-7	Bisphenol A, inhalable dust	-	2		TWA (8 h)	WEL
108-95-2	Phenol	2	7.8		TWA (8 h)	WEL
		4	16		STEL (15 min)	WEL

### **DNEL/DMEL values**

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
1950616-36- 0	Formaldehyde, oligomeric reaction products with phe	enol and m-phenylene	ebis(methylamine)	
Worker DNEL	_, long-term	inhalation	systemic	0,02 mg/m <sup>3</sup>
Worker DNEL	_, acute	inhalation	systemic	2,0 mg/m <sup>3</sup>
Worker DNEL	_, long-term	inhalation	local	0,6 mg/m <sup>3</sup>
Worker DNEL	_, acute	inhalation	local	6,0 mg/m <sup>3</sup>
Worker DNEL	_, acute	dermal	local	2,8 mg/person/day
Worker DNEL	., long-term	dermal	local	0,28 mg/person/day
Worker DNEL	_, acute	dermal	systemic	mg/kg bw/day
1477-55-0	m-Phenylenebis(methylamine)			
Worker DNEL	_, long-term	inhalation	systemic	1,2 mg/m <sup>3</sup>
Worker DNEL	_, long-term	inhalation	local	0,2 mg/m <sup>3</sup>
Worker DNEL	., long-term	dermal	systemic	0,33 mg/kg bw/day

# **PNEC** values

CAS No	Substance				
Environme	ntal compartment	Value			
1477-55-0	m-Phenylenebis(methylamine)				
Freshwater		0,094 mg/l			
Marine wat	er	0,009 mg/l			
Freshwater	rsediment	0,43 mg/kg			
Marine sed	iment	0,043 mg/kg			
Micro-orga	nisms in sewage treatment plants (STP)	10 mg/l			
Soil		0,045 mg/kg			
90-72-2	2,4,6-Tris(dimethylaminomethyl)phenol				
Freshwater		0,084 mg/l			
Marine wat	er	0,0084 mg/l			
Micro-orga	nisms in sewage treatment plants (STP)	0,2 mg/l			

# Additional advice on limit values

This mixture contains quartz filler which is firmly bound in the pasty component, and thus not freely available during use, so that a risk of dust inhalation is excluded. Exposure limit values for respirable dusts are not relevant for this product.

### 8.2. Exposure controls



according to Regulation (EC) No 1907/2006

# PEC-III, Comp. B

Page 7 of 16

### Revision date: 11.12.2020







#### Appropriate engineering controls

Provide adequate ventilation. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

#### Protective and hygiene measures

Take off contaminated clothing and wash it before reuse. Draw up and observe skin protection programme. Wash hands thoroughly after handling. When using do not eat, drink or smoke. Avoid contact during pregnancy and while nursing.

#### Eye/face protection

Wear eye protection/face protection. Wear safety glasses.

### Hand protection

Recommended material: NBR (Nitrile rubber) Breakthrough time: > 480 min Thickness of the glove material: 0,7 mm DIN-/EN-Norms: EN 374

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

#### Skin protection

Wear suitable protective clothing.

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection. Respiratory protection with combination filter A1P2 (organic gases/vapors and particles) recommended.

#### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

solid (pasty) black / red characteristic No data available	not applicable
	not determined
	not determined
	not applicable
	not determined not applicable
	not determined
	not determined
	not determined not applicable not determined
	black / red characteristic



F

# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# PEC-III, Comp. B

Page 8 of 16

Revision date: 11.12.2020	
Oxidizing properties Not oxidising.	
Vapour pressure:	not determined
Density (at 20 °C):	1,07 g/cm³
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.
Solubility in other solvents not determined	
Partition coefficient:	not determined
Vapour density:	not determined
Evaporation rate:	not determined
9.2. Other information	
Solid content:	not determined

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

see section 10.3

#### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

#### 10.3. Possibility of hazardous reactions

Violent reaction with: Oxidising agent, strong

# 10.4. Conditions to avoid

see section 7.2

# 10.5. Incompatible materials

Oxidising agent, strong

#### 10.6. Hazardous decomposition products

No known hazardous decomposition products.

#### **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

#### Acute toxicity

Harmful if swallowed.



Page 9 of 16

# according to Regulation (EC) No 1907/2006

# PEC-III, Comp. B

Revision date: 11.12.2020

CAS No	Chemical name								
	Exposure route	Dose		Species	Source	Method			
2855-13-2	3-aminomethyl-3,5,5-tr	imethylcyc	lohexylamir	ie					
	oral	LD50 mg/kg	1030	Rat					
	dermal	ATE mg/kg	1100						
1477-55-0	m-Phenylenebis(methy	(lamine)							
	oral	LD50 mg/kg	930	Rat					
	dermal	LD50 mg/kg	2000	Rabbit					
	inhalation (1 h) vapour	LC50	3,89 mg/l	Rat					
	inhalation aerosol	ATE	1,5 mg/l						
90-72-2	2,4,6-Tris(dimethylamir	nomethyl)p	henol						
	oral	LD50 mg/kg	2169	Rat					
	dermal	LD50 mg/kg	1280	Rat					
100-51-6	Benzyl alcohol								
	oral	LD50 mg/kg	1230	Rat					
	inhalation vapour	ATE	11 mg/l						
	inhalation aerosol	ATE	1,5 mg/l						
111-40-0	Diethylenetriamine	Diethylenetriamine							
	oral	LD50 mg/kg	1080	Rat					
	dermal	LD50 mg/kg	1054	Rabbit					
	inhalation vapour	ATE	0,5 mg/l						
	inhalation aerosol	ATE	0,05 mg/l						
108-95-2	Phenol								
	oral	LD50 mg/kg	650	Rat		OECD 401			
	dermal	LD50 mg/kg	630	Rabbit					
	inhalation vapour	ATE	3 mg/l						
	inhalation aerosol	LC50	0,9 mg/l	8 h Rat					
80-05-7	Bisphenol A								
	oral	LD50 mg/kg	3250	Rat					
	dermal	LD50 mg/kg	3000	Rabbit					

Irritation and corrosivity Causes severe skin burns and eye damage. Causes serious eye damage.

Sensitising effects



according to Regulation (EC) No 1907/2006

# PEC-III, Comp. B

Revision date: 11.12.2020

Page 10 of 16

May cause an allergic skin reaction. (3-aminomethyl-3,5,5-trimethylcyclohexylamine; Formaldehyde, oligomeric reaction products with phenol and m-phenylenebis(methylamine); m-Phenylenebis(methylamine); Formaldehyde, oligomeric reaction products with 4,4<sup>-</sup>-isopropylidenediphenol and diethylenetriamine; Diethylenetriamine; Bisphenol A)

### Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing genetic defects. (Phenol) May damage fertility. (Bisphenol A) Carcinogenicity: Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

#### **STOT-repeated exposure**

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### **Further information**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

This mixture is place on the market in a form in which aerosol formation cannot occur during intended use and may only be used for applications in which aerosol formation is excluded. Workplace measurements to determine the exposure of users towards contained hazardous substances were carried out. Test reports show no need for the classification of the product as toxic by inhalation. The test reports are available. According to Article 6 of Regulation EC No. 1272/2008, classification and labeling as inhalation toxic is therefore not required.

#### **SECTION 12: Ecological information**

#### 12.1. Toxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.



Page 11 of 16

# according to Regulation (EC) No 1907/2006

# PEC-III, Comp. B

Revision date: 11.12.2020

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method
1477-55-0	m-Phenylenebis(methylamine)						
	Acute fish toxicity	LC50 mg/l	87,6	96 h	Oryzias latipes (Ricefish)		OECD 203
	Acute algae toxicity	ErC50 mg/l	32,1	72 h	Selenastrum capricornutum		OECD 201
	Acute crustacea toxicity	EC50 mg/l	15,2		Daphnia magna (Big water flea)		OECD 202
	Crustacea toxicity	NOEC	4,7 mg/l		Daphnia magna (Big water flea)		OECD 211
90-72-2	2,4,6-Tris(dimethylamine	omethyl)pl	henol				
	Acute fish toxicity	LC50	175 mg/l	96 h	Cyprinus carpio (Common Carp)		
	Acute algae toxicity	ErC50	84 mg/l	72 h	Desmodesmus subspicatus		OECD 201
	Algae toxicity	NOEC mg/l	6,25	3 d			
111-40-0	Diethylenetriamine						
	Acute fish toxicity	LC50	430 mg/l		Leuciscus idus		
	Acute algae toxicity	ErC50 mg/l	1164	72 h	Selenastrum capricornutum		
	Acute crustacea toxicity	EC50 mg/l	53,5	48 h	Daphnia magna		
108-95-2	Phenol						
	Acute fish toxicity	LC50	8,9 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Acute algae toxicity	ErC50 mg/l	61,1	96 h			
	Acute crustacea toxicity	EC50	3,1 mg/l		Daphnia magna (Big water flea)		
	Crustacea toxicity	NOEC mg/l	0,16		Daphnia magna (Big water flea)		
80-05-7	Bisphenol A						
	Acute fish toxicity	LC50	4,6 mg/l	96 h	Pimephales promelas		
	Acute algae toxicity	ErC50 mg/l	2,73	96 h	Selenastrum capricornutum		
	Acute crustacea toxicity	EC50 mg/l	10,2	48 h	Daphnia magna		

### 12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
80-05-7	Bisphenol A			
	OECD 301F	74,7 - 81,4	28	

# 12.3. Bioaccumulative potential

The product has not been tested.



according to Regulation (EC) No 1907/2006

# PEC-III, Comp. B

Page 12 of 16

### Revision date: 11.12.2020

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	1,9
1477-55-0	m-Phenylenebis(methylamine)	0,18
90-72-2	2,4,6-Tris(dimethylaminomethyl)phenol	0,219
100-51-6	Benzyl alcohol	1,05
111-40-0	Diethylenetriamine	-5,58
108-95-2	Phenol	1,5
80-05-7	Bisphenol A	3,4

#### BCF

CAS No	Chemical name	BCF	Species	Source
1477-55-0	m-Phenylenebis(methylamine)	2,69		
108-95-2	Phenol	17,5		
80-05-7	Bisphenol A	73		

### 12.4. Mobility in soil

The product has not been tested.

#### 12.5. Results of PBT and vPvB assessment

The product has not been tested.

### 12.6. Other adverse effects

No information available.

#### Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

#### **Disposal recommendations**

Subsequent waste code numbers of the European Waste Catalogue are considered as recommendations. Dispose of waste according to applicable legislation. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

#### List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

#### List of Wastes Code - used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

#### List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

### **SECTION 14: Transport information**



according to Regulation (EC) No 1907/2006

	PEC-III, Comp. B
Revision date: 11.12.2020	Page 13 of 16
Land transport (ADR/RID)	
14.1. UN number:	UN 3259
14.2. UN proper shipping name:	AMINES, SOLID, CORROSIVE, N.O.S. (m-Phenylenebis(methylamine))
14.3. Transport hazard class(es):	8
14.4. Packing group:	ll
Hazard label:	8
Classification code:	C8
Special Provisions:	274
Limited quantity: Excepted quantity:	1 kg E2
Transport category:	2
Hazard No:	80
Tunnel restriction code:	E
Inland waterways transport (ADN)	
<u>14.1. UN number:</u>	UN 3259
14.2. UN proper shipping name:	AMINES, SOLID, CORROSIVE, N.O.S. (m-Phenylenebis(methylamine))
14.3. Transport hazard class(es):	8
<u>14.4. Packing group:</u> Hazard label:	 8
Classification code:	C8
Special Provisions:	274
Limited quantity:	1 kg
Excepted quantity:	E2
Marine transport (IMDG)	
<u>14.1. UN number:</u>	UN 3259
14.2. UN proper shipping name:	AMINES, SOLID, CORROSIVE, N.O.S. (m-Phenylenebis(methylamine))
14.3. Transport hazard class(es):	8
14.4. Packing group:	
Hazard label:	
Special Provisions:	274
Limited quantity:	1 kg
Excepted quantity: EmS:	E2 F-A, S-B
Air transport (ICAO-TI/IATA-DGR)	
<u>14.1. UN number:</u>	UN 3259
14.2. UN proper shipping name:	AMINES, SOLID, CORROSIVE, N.O.S. (m-Phenylenebis(methylamine))
14.3. Transport hazard class(es):	8
14.4. Packing group:	



according to Regulation (EC) No 1907/2006

# PEC-III, Comp. B

	PEC-III, C	отр. в	
Revision date: 11.12.2020			Page 14 of 16
Hazard label:	8		
Special Provisions: Limited quantity Passenger: Passenger LQ: Excepted quantity:	A3 Å803 5 kg Y844 E2		
IATA-packing instructions - Passenger: IATA-max. quantity - Passenger: IATA-packing instructions - Cargo: IATA-max. quantity - Cargo:		859 15 kg 863 50 kg	
14.5. Environmental hazards			
ENVIRONMENTALLY HAZARDOUS:	no		
14.6. Special precautions for user Warning: strongly corrosive.			
14.7. Transport in bulk according to An	nex II of Marpol an	d the IBC Code	
not applicable			
SECTION 15: Regulatory informatio	n		
15.1. Safety, health and environmental	regulations/legisla	tion specific for the substance or mixture	9
<b>EU regulatory information</b> Authorisations (REACH, annex XIV): Substances of very high concern, S Bisphenol A	VHC (REACH, artic	le 59):	
alcohol; Diethylenetriamine Entry 66: Bisphenol A	hylcyclohexylamine	2,4,6-Tris(dimethylaminomethyl)phenol; Be	nzyl
Information according to 2012/18/EU (SEVESO III):	NOT SUDJECT TO 201	2/18/EU (SEVESO III)	
Additional information			
VOC content: 28,7 % (DIN EN ISO	11890-2)		
To follow: 850/2004/EC , 79/117/EE	C , 689/2008/EC		
National regulatory information	,		
Employment restrictions:	work protection gu	ns to employment for juveniles according to t ideline' (94/33/EC). Observe employment re y Protection Directive (92/85/EEC) for expec	strictions
Water hazard class (D): Skin resorption/Sensitization:	2 - obviously haza Causes allergic hy	rdous to water persensitivity reactions.	
15.2. Chemical safety assessment			
Chemical safety assessments for su	ubstances in this mi	xture were not carried out.	
SECTION 16: Other information			

### Abbreviations and acronyms

ADN: Accord européen relativ au transport international des marchandises Dangereuses par voie de

according to Regulation (EC) No 1907/2006

# PEC-III, Comp. B

Revision date: 11.12.2020

Page 15 of 16

Navigation (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways) ADR: Accord européen sur le transport des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) CAS: Chemical Abstracts Service CLP: Classification, Labeling and Packaging DMEL: Derived Minimal Effect level **DNEL: Derived No Effect Level** EC50: Effective concentration, 50% IATA: International Air Transport Association IATA-DGR: Dangerous Goods Regulations (DRG) for the air transport (IATA) IMDG: International Maritime Dangerous Goods Code LC50: Lethal concentration, 50% LD50: Lethal dose, 50% NOEC: No Observed Effect Concentration OECD: Oragnisation for Economic Co-operation and Development PBT: persistent, bioaccumulative and toxic vPvB: very persistent and very bioaccumulative PNEC: Predicted No Effect Concentration REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals RID: Règlement concernant le transport international ferroviaire des marchandises dangereuses (Regulations Concerning the International Carriage of Dangerous Goods by Rail) VOC: Volatile organic compound Acute Tox. 2: Acute toxicity, Category 2 Acute Tox. 3: Acute toxicity, Category 3 Acute Tox. 4: Acute toxicity, Category 4 Aquatic Chronic 3: Long-term aquatic hazard, Category 3 Eye Dam. 1: Serious eye damage/eye irritation, Category 1 Eye Irrit. 2: Serious eye damage/eye irritation, Category 2 Repr. 1B: Reproductive toxicity, Category 1B Skin Sens. 1: Skin sensitilization, Category 1 Skin Sens. 1B: Skin sensitilization, Category 1B STOT RE 2: Specific target organ toxicity (repeated exposure), Category 2 STOT SE 3: Specific target organ toxicity (single exposure), Category 3

#### Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Acute Tox. 4; H302	Calculation method
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1; H317	Calculation method
Muta. 2; H341	Calculation method
Repr. 1B; H360F	Calculation method
Aquatic Chronic 3; H412	Calculation method

#### Relevant H and EUH statements (number and full text)

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.



Page 16 of 16

according to Regulation (EC) No 1907/2006

# PEC-III, Comp. B

Revision date: 11.12.2020

H330 Fatal if inhaled. Toxic if inhaled. H331 H332 Harmful if inhaled. H335 May cause respiratory irritation. H341 Suspected of causing genetic defects. H360F May damage fertility. Suspected of damaging fertility. H361f May cause damage to organs through prolonged or repeated exposure. H373 Toxic to aquatic life with long lasting effects. H411 H412 Harmful to aquatic life with long lasting effects.

### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)