



according to Regulation (EC) No 1907/2006

PES-III, Comp. A

Revision date: 11.12.2020 Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

PES-III, Comp. A

UFI: 8NPV-10QN-8009-D2RJ

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesive mortar for fastening elements A-component (resin)

Uses advised against

no restriction

1.3. Details of the supplier of the safety data sheet

Company name: UIP Verbindungstechnik GmbH

Street: Kapellenstraße 47 Place: D-65830 Kriftel

Telephone: +49 6192 9578050 Telefax:+49 6192 9578055

e-mail: office@uip-systems.com Internet: www.uip-systems.com

1.4. Emergency telephone +49 (0)551-19240 (GIZ-Nord, German and English, 24/7)

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2 Respiratory or skin sensitisation: Skin Sens. 1

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:
Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.

Toxic to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane;

1,6-hexanediol diglycidyl ether **Signal word:** Warning

Pictograms:





Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation. H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.



according to Regulation (EC) No 1907/2006

PES-III, Comp. A

Revision date: 11.12.2020 Page 2 of 11

Precautionary statements

P264 Wash hands thoroughly after handling. P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P391 Collect spillage.

2.3. Other hazards

People who are allergic to epoxide should avoid the use of the product.

Use only outdoors or in a well-ventilated area.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
1675-54-3	2,2'-[(1-methylethylidene)bis(4,	1-phenyleneoxymethylene)]bisoxi	rane	30 - < 60 %
	216-823-5	603-073-00-2	01-2119456619-26	
	Skin Irrit. 2, Eye Irrit. 2, Skin Se	ns. 1, Aquatic Chronic 2; H315 H	319 H317 H411	
16096-31-4	1,6-hexanediol diglycidyl ether			10 - < 15 %
	240-260-4		01-2119463471-41	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 3; H315 H319 H317 H412			

Full text of H and EUH statements: see section 16.

Specific concentration limits and M-factors

CAS No	EC No	Chemical name	Quantity
	Specific conce	entration limits and M-factors	
1675-54-3	216-823-5	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	30 - < 60 %
	Skin Irrit. 2; H	315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Take off immediately all contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eyes


In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Medical treatment necessary.

4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation.





according to Regulation (EC) No 1907/2006

PES-III, Comp. A

Revision date: 11.12.2020 Page 3 of 11

May cause an allergic skin reaction. Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam

Extinguishing powder

Water spray jet

Carbon dioxide (CO2)

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Pyrolysis products, toxic

Carbon monoxide

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Provide adequate ventilation.

6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Collect spillage. Take up mechanically, placing in appropriate containers for disposal. Suitable material for taking up: Sand

Treat the recovered material as prescribed in the section on waste disposal.

Retain contaminated washing water and dispose it.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only outdoors or in a well-ventilated area.

Wear personal protection equipment (refer to section 8).

Avoid contact with skin, eyes and clothes.

When using do not eat, drink or smoke.

7.2. Conditions for safe storage, including any incompatibilities



according to Regulation (EC) No 1907/2006

PES-III, Comp. A

Revision date: 11.12.2020 Page 4 of 11

Requirements for storage rooms and vessels

Keep container tightly closed.

Store in a place accessible by authorized persons only.

Keep only in the original container in a cool, well-ventilated place.

Hints on joint storage

Do not store together with: Oxidising agent, strong

Do not use for products which come into contact with the food stuffs.

Further information on storage conditions

storage temperature: 5 - 35°C

7.3. Specific end use(s)

Adhesive mortar for fastening elements A-component (resin)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
16096-31-4	1,6-hexanediol diglycidyl ether			
Worker DNEL	., long-term	inhalation	systemic	10,57 mg/m ³
Worker DNEL	., long-term	inhalation	local	0,44 mg/m ³
Worker DNEL	., long-term	dermal	systemic	6,0 mg/kg bw/day
Worker DNEL, long-term		dermal	local	0,0226 mg/cm ²
Consumer DNEL, long-term		inhalation	systemic	5,29 mg/m ³
Consumer DNEL, long-term		inhalation	local	0,27 mg/m ³
Consumer DN	IEL, long-term	dermal	systemic	3,0 mg/kg bw/day
Consumer DN	IEL, long-term	dermal	local	0,0136 mg/cm ²
Consumer DN	IEL, acute	inhalation	systemic	5,29 mg/m ³
Consumer DN	IEL, acute	dermal	systemic	1,7 mg/kg bw/day
Consumer DN	IEL, acute	dermal	local	0,0136 mg/cm ²
Consumer DN	IEL, long-term	oral	systemic	1,5 mg/kg bw/day
Consumer DN	NEL, acute	oral	systemic	1,5 mg/kg bw/day

PNEC values

CAS No	Substance			
Environmenta	Environmental compartment Value			
16096-31-4	1-4 1,6-hexanediol diglycidyl ether			
Freshwater 0,0115 mg/l				
Marine water 0,00115 mg		0,00115 mg/l		
Freshwater sediment (0,283 mg/kg		
Marine sedim	ent	0,283 mg/kg		

Additional advice on limit values

This mixture contains quartz filler which is firmly bound in the pasty component, and thus not freely available during use, so that a risk of dust inhalation is excluded. Exposure limit values for respirable dusts are not relevant for this product.

8.2. Exposure controls



according to Regulation (EC) No 1907/2006

PES-III, Comp. A

Revision date: 11.12.2020 Page 5 of 11







Appropriate engineering controls

Provide adequate ventilation. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

Protective and hygiene measures

Take off contaminated clothing and wash it before reuse. Draw up and observe skin protection programme. Wash hands thoroughly after handling. When using do not eat, drink or smoke.

Eye/face protection

Wear eye protection/face protection. Wear safety glasses.

Hand protection

Recommended material: NBR (Nitrile rubber)

Breakthrough time: > 480 min

Thickness of the glove material: 0,7 mm

DIN-/EN-Norms: EN 374

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Respiratory protection with combination filter A1P2 (organic gases/vapors and particles) recommended.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: solid (pasty)
Colour: light beige
Odour: characteristic
Odour threshold: No data available

pH-Value: not determined

Changes in the physical state

Melting point:
Initial boiling point and boiling range:
not determined
not determined
not applicable

Flammability

Solid: not determined
Gas: not applicable

Explosive properties

The product is not: Explosive.

Lower explosion limits:

Upper explosion limits:

not determined

not determined

Auto-ignition temperature

Solid: not determined
Gas: not applicable



according to Regulation (EC) No 1907/2006

PES-III, Comp. A

Revision date: 11.12.2020 Page 6 of 11

Decomposition temperature: not determined

Oxidizing properties

Not oxidising.

Vapour pressure: not determined

Density (at 20 °C): 1,45 g/cm³

Water solubility: The study does not need to be conducted because the substance is known to be

insoluble in water.

Solubility in other solvents

not determined

Partition coefficient: not determined
Vapour density: not determined
Evaporation rate: not determined

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Violent reaction with: Oxidising agent, strong

10.4. Conditions to avoid

Heat. Keep cool. Protect from sunlight.

10.5. Incompatible materials

Keep away from: Oxidizing agent

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name						
	Exposure route	Dose		Species	Source	Method	
16096-31-4	1,6-hexanediol diglycid	yl ether					
	- · · ·	LD50 mg/kg	2190	Rat		OECD 401	
		LD50 mg/kg	> 2000	Rat		OECD 402	
	inhalation (4 h) vapour	LC50 mg/l	0,035	Rat			

Irritation and corrosivity



according to Regulation (EC) No 1907/2006

PES-III, Comp. A

Revision date: 11.12.2020 Page 7 of 11

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

May cause an allergic skin reaction. (2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane; 1,6-hexanediol diglycidyl ether)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

Toxic to aquatic life with long lasting effects.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
16096-31-4	1,6-hexanediol diglycidy	l ether					
	Acute fish toxicity	LC50	30 mg/l		Oncorhynchus mykiss (Rainbow trout)		
	Acute crustacea toxicity	EC50	47 mg/l		Daphnia magna (Big water flea)		

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
16096-31-4	1,6-hexanediol diglycidyl ether			
	OECD 301D	71 %	28	

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
16096-31-4	1,6-hexanediol diglycidyl ether	0,822

BCF

CAS No	Chemical name	BCF	Species	Source
16096-31-4	1,6-hexanediol diglycidyl ether	3,57		

12.4. Mobility in soil


The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.





according to Regulation (EC) No 1907/2006

PES-III, Comp. A

Revision date: 11.12.2020 Page 8 of 11

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Subsequent waste code numbers of the European Waste Catalogue are considered as recommendations. Dispose of waste according to applicable legislation. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances;

hazardous waste

List of Wastes Code - used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances;

hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by

hazardous substances; hazardous waste

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 3077

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

(Epoxy resin)

14.3. Transport hazard class(es): 9

14.4. Packing group:

Hazard label: 9



Classification code:

assincation code:

Special Provisions: 274 335 375 601

Limited quantity: 5 kg
Excepted quantity: E1
Transport category: 3
Hazard No: 90
Tunnel restriction code: -

Other applicable information (land transport)

No dangerous goods in packaging until 5 kg according special instruction 375 ADR/RID

Inland waterways transport (ADN)

14.1. UN number: UN 3077



according to Regulation (EC) No 1907/2006

PES-III, Comp. A

Revision date: 11.12.2020 Page 9 of 11

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

(Epoxy resin)

14.3. Transport hazard class(es):914.4. Packing group:IIIHazard label:9



Classification code: M7

Special Provisions: 274 335 375 601

Limited quantity: 5 kg
Excepted quantity: E1

Other applicable information (inland waterways transport)

No dangerous goods in packaging until 5 kg according special instruction 375 ADN

Marine transport (IMDG)

14.1. UN number: UN 3077

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

(Epoxy resin)

14.3. Transport hazard class(es):914.4. Packing group:IIIHazard label:9



Special Provisions: 274, 335, 966, 967, 969

Limited quantity: 5 kg
Excepted quantity: E1
EmS: F-A, S-F

Other applicable information (marine transport)

No dangerous goods in packaging until 5kg according 2.10.2.7 IMDG Code

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 3077

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

(Epoxy resin)


14.3. Transport hazard class(es):914.4. Packing group:IIIHazard label:9



Special Provisions: A97 A158 A179 A197

Limited quantity Passenger: 30 kg G Passenger LQ: Y956 Excepted quantity: E1

IATA-packing instructions - Passenger:956IATA-max. quantity - Passenger:400 kgIATA-packing instructions - Cargo:956IATA-max. quantity - Cargo:400 kg





according to Regulation (EC) No 1907/2006

PES-III, Comp. A

Revision date: 11.12.2020 Page 10 of 11

Other applicable information (air transport)

No dangerous goods in packaging until 5 kg according A197 IATA-DGA

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes



14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Information according to 2012/18/EU
E2 Hazardous to the Aquatic Environment (SEVESO III):

Additional information

VOC content: < 0,1 % (DIN EN ISO 11890-2)

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADN: Accord européen relativ au transport international des marchandises Dangereuses par voie de Navigation

(European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)

ADR: Accord européen sur le transport des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

BCF: Bioconcentration factor CAS: Chemical Abstracts Service

CLP: Classification, Labeling and Packaging

DMEL: Derived Minimal Effect level DNEL: Derived No Effect Level EC50: Effective concentration, 50%

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations (DRG) for the air transport (IATA)

ICAO: International Civil Aviation Organization

IC50: Inhibitory concentration, 50%

IMDG: International Maritime Code for Dangerous Goods

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%



UIP Verbindungstechnik GmbH

according to Regulation (EC) No 1907/2006

PES-III, Comp. A

Revision date: 11.12.2020 Page 11 of 11

NOEC: No Observed Effect Concentration

OECD: Oragnisation for Economic Co-operation and Development

PBT: persistent, bioaccumulative and toxic vPvB: very persistent and very bioaccumulative PNEC: Predicted No Effect Concentration

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

RID: Règlement concernant le transport international ferroviaire de marchandises dangereuses (Regulations

Concerning the International Carriage of Dangerous Goods by Rail)

VOC: Volatile organic compound

Aquatic Chronic 2: Long-term aquatic hazard, Category 2 Aquatic Chronic 3: Long-term aquatic hazard, Category 3 Eye Irrit. 2: Serious eye damage/eye irritation, Category 2 Skin Irrit. 2: Serious eye damage/eye irritation, Category 2

Skin Sens. 1: Skin sensitilization, Category 1

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)


H315	Gauses skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)





according to Regulation (EC) No 1907/2006

PES-III, Comp. B

Revision date: 11.12.2020 Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

PES-III, Comp. B

UFI: WRPV-J0E1-J00S-1EAM

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

compound mortar B-component (hardener)

Uses advised against

no restriction

1.3. Details of the supplier of the safety data sheet

Company name: UIP Verbindungstechnik GmbH

Street: Kapellenstraße 47 Place: D-65830 Kriftel

Telephone: +49 6192 9578050 Telefax:+49 6192 9578055

e-mail: office@uip-systems.com Internet: www.uip-systems.com

1.4. Emergency telephone +49 (0)551-19240 (GIZ-Nord, German and English, 24/7)

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Acute toxicity: Acute Tox. 4

Skin corrosion/irritation: Skin Corr. 1

Serious eye damage/eye irritation: Eye Dam. 1 Respiratory or skin sensitisation: Skin Sens. 1

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements: Harmful if swallowed.

Causes severe skin burns and eye damage.

Causes serious eye damage.

May cause an allergic skin reaction.

Harmful to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine;

m-Phenylenebis(methylamine);

2,4,6-Tris(dimethylaminomethyl)phenol

Signal word: Danger

Pictograms:





Hazard statements

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.



according to Regulation (EC) No 1907/2006

PES-III, Comp. B

Revision date: 11.12.2020 Page 2 of 12

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

or shower.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P501 Dispose of contents/container to an approved waste disposal plant in accordance with

local/national regulation.

2.3. Other hazards

Contains Amines. May produce an allergic reaction. Use only outdoors or in a well-ventilated area.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity		
	EC No	Index No	REACH No			
	GHS Classification					
25513-64-8	2,2,4(or 2,4,4)-trimethylhexane	-1,6-diamine		25 - < 35 %		
	247-063-2		01-2119560598-25			
	Acute Tox. 4, Skin Corr. 1, Eye H412	Acute Tox. 4, Skin Corr. 1, Eye Dam. 1, Skin Sens. 1, Aquatic Chronic 3; H302 H314 H318 H317 H412				
1477-55-0	m-Phenylenebis(methylamine)			1 - < 8 %		
	216-032-5		01-2119480150-50			
	Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1B, Aquatic Chronic 3; H332 H302 H314 H318 H317 H412					
90-72-2	2,4,6-Tris(dimethylaminomethyl)phenol			5 - < 10 %		
	202-013-9		01-2119560597-27			
	Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2; H302 H315 H319					
104-15-4	p-Toluenesulphonic acid			1 - < 5 %		
	203-180-0	016-030-00-2	01-2119538811-39			
	Skin Irrit. 2, Eye Irrit. 2, STOT SE 3; H315 H319 H335					

Full text of H and EUH statements: see section 16.

Specific concentration limits and M-factors


CAS No	EC No	Chemical name	Quantity		
	Specific conce	Specific concentration limits and M-factors			
104-15-4	203-180-0	p-Toluenesulphonic acid	1 - < 5 %		
	STOT SE 3; H				

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Remove affected person from the danger area and lay down. Take off immediately all contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.





according to Regulation (EC) No 1907/2006

PES-III, Comp. B

Revision date: 11.12.2020 Page 3 of 12

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eves

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Medical treatment necessary.

4.2. Most important symptoms and effects, both acute and delayed

Harmful if swallowed.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam

Extinguishing powder

Water spray jet

Carbon dioxide (CO2)

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Pyrolysis products, toxic

Carbon monoxide

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Provide adequate ventilation.

6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Collect spillage. Take up mechanically, placing in appropriate containers for disposal. Suitable material for taking up: Sand


Treat the recovered material as prescribed in the section on waste disposal.

Retain contaminated washing water and dispose it.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8





according to Regulation (EC) No 1907/2006

PES-III, Comp. B

Revision date: 11.12.2020 Page 4 of 12

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only outdoors or in a well-ventilated area.

Wear personal protection equipment (refer to section 8).

Avoid contact with skin, eyes and clothes.

When using do not eat, drink or smoke.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed.

Store in a place accessible by authorized persons only.

Keep only in the original container in a cool, well-ventilated place.

Hints on joint storage

Do not store together with: Oxidising agent, strong, Organic peroxides Do not use for products which come into contact with the food stuffs.

Further information on storage conditions

Keep container tightly closed in a cool place.

storage temperature: 5 - 35°C

7.3. Specific end use(s)

see section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
25513-64-8	2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine			
Consumer DI	NEL, long-term	oral	systemic	0,05 mg/kg bw/day
1477-55-0	m-Phenylenebis(methylamine)			
Worker DNEI	L, long-term	inhalation	systemic	1,2 mg/m ³
Worker DNEI	L, long-term	inhalation	local	0,2 mg/m ³
Worker DNEI	L, long-term	dermal	systemic	0,33 mg/kg bw/day
104-15-4	p-Toluenesulphonic acid			
Worker DNEI	L, long-term	dermal	systemic	7,6 mg/kg bw/day
Worker DNEI	Worker DNEL, long-term		systemic	53,6 mg/m ³
Consumer DNEL, long-term		dermal	systemic	2,5 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	8,7 mg/m ³
Consumer DNEL, long-term		oral	systemic	0,05 mg/kg bw/day



according to Regulation (EC) No 1907/2006

PES-III, Comp. B

Revision date: 11.12.2020 Page 5 of 12

PNEC values

CAS No	Substance	
Environmen	tal compartment	Value
25513-64-8	2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	
Freshwater		0,102 mg/l
Marine wate	r	0,01 mg/l
Freshwater	sediment	0,662 mg/kg
Marine sedir	ment	0,062 mg/kg
Micro-organi	isms in sewage treatment plants (STP)	72 mg/l
1477-55-0	m-Phenylenebis(methylamine)	
Freshwater		0,094 mg/l
Marine wate	r	0,009 mg/l
Freshwater sediment 0,43 mg/k		0,43 mg/kg
Marine sediment 0,		0,043 mg/kg
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		0,045 mg/kg
90-72-2	2,4,6-Tris(dimethylaminomethyl)phenol	
Freshwater		0,084 mg/l
Marine wate	r	0,0084 mg/l
Micro-organi	isms in sewage treatment plants (STP)	0,2 mg/l
104-15-4	p-Toluenesulphonic acid	
Freshwater		0,073 mg/l
Marine wate	r	0,0073 mg/l
Freshwater sediment 0,05		0,0577 mg/kg
Marine sediment 0,00577 mg.		
Soil 0,016 mg/kg		

Additional advice on limit values

This mixture contains quartz filler which is firmly bound in the pasty component, and thus not freely available during use, so that a risk of dust inhalation is excluded. Exposure limit values for respirable dusts are not relevant for this product.

8.2. Exposure controls







Appropriate engineering controls

Provide adequate ventilation. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

Protective and hygiene measures


Take off contaminated clothing and wash it before reuse. Draw up and observe skin protection programme. Wash hands thoroughly after handling. When using do not eat, drink or smoke.

Eye/face protection

Wear eye/face protection. Wear safety glasses.

Hand protection

Recommended material: NBR (Nitrile rubber)





according to Regulation (EC) No 1907/2006

PES-III, Comp. B

Revision date: 11.12.2020 Page 6 of 12

Breakthrough time: > 480 min

Thickness of the glove material: 0,7 mm

DIN-/EN-Norms: EN 374

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Respiratory protection with combination filter A1P2 (organic gases/vapors and particles) recommended.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: solid (pasty)
Colour: grey / red
Odour: characteristic
Odour threshold: No data available

pH-Value: not determined

Changes in the physical state

Melting point:

Initial boiling point and boiling range:

Flash point:

not determined

not determined

not applicable

Flammability

Solid: not determined
Gas: not applicable
Lower explosion limits: not determined
Upper explosion limits: not determined

Auto-ignition temperature

Solid: not determined
Gas: not applicable

Decomposition temperature: not determined

Oxidizing properties

Not oxidising.

Vapour pressure: not determined

Density (at 20 °C): 1,42 g/cm³

Water solubility:

The study does not need to be conducted because the substance is known to be

insoluble in water.

Solubility in other solvents

not determined

Partition coefficient: not determined Vapour density: not determined Evaporation rate: not determined

9.2. Other information

Solid content: not determined



according to Regulation (EC) No 1907/2006

PES-III, Comp. B

Revision date: 11.12.2020 Page 7 of 12

SECTION 10: Stability and reactivity

10.1. Reactivity

see section 10.3

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Violent reaction with: Oxidising agent

10.4. Conditions to avoid

see section 7.2

10.5. Incompatible materials

Oxidising agent, strong

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Harmful if swallowed.

ATEmix calculated

ATE (oral) 1051,3 mg/kg

	,					
CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
25513-64-8	2,2,4(or 2,4,4)-trimethy	lhexane-1,6	6-diamine			
		ATE mg/kg	500			
1477-55-0	m-Phenylenebis(methy	m-Phenylenebis(methylamine)				
	oral	LD50 mg/kg	930	Rat		
	dermal	LD50 mg/kg	2000	Rabbit		
	inhalation (1 h) vapour	LC50	3,89 mg/l	Rat		
	inhalation aerosol	ATE	1,5 mg/l			
90-72-2	2,4,6-Tris(dimethylaminomethyl)phenol					
	oral	LD50 mg/kg	2169	Rat		
	dermal	LD50 mg/kg	1280	Rat		

Irritation and corrosivity

Causes severe skin burns and eye damage.

Causes serious eye damage.

Sensitising effects

May cause an allergic skin reaction. (2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine; m-Phenylenebis(methylamine))

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

UIP Verbindungstechnik GmbH

according to Regulation (EC) No 1907/2006

PES-III, Comp. B

Revision date: 11.12.2020 Page 8 of 12

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CAS No	Chemical name								
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method		
25513-64-8	2,2,4(or 2,4,4)-trimethyll	2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine							
	Acute algae toxicity	ErC50 mg/l	43,5		Selenastrum capricornutum		OECD 201		
	Fish toxicity	NOEC mg/l	10,9	30 d	Brachydanio rerio (zebra-fish)		OECD 210		
	Crustacea toxicity	NOEC mg/l	1,02		Daphnia magna (Big water flea)		OECD 211		
1477-55-0	m-Phenylenebis(methylamine)								
	Acute fish toxicity	LC50 mg/l	87,6		Oryzias latipes (Ricefish)		OECD 203		
	Acute algae toxicity	ErC50 mg/l	32,1		Selenastrum capricornutum		OECD 201		
	Acute crustacea toxicity	EC50 mg/l	15,2		Daphnia magna (Big water flea)		OECD 202		
	Crustacea toxicity	NOEC	4,7 mg/l		Daphnia magna (Big water flea)		OECD 211		
90-72-2	2,4,6-Tris(dimethylaminomethyl)phenol								
	Acute fish toxicity	LC50	175 mg/l	96 h	Cyprinus carpio (Common Carp)				
	Acute algae toxicity	ErC50	84 mg/l		Desmodesmus subspicatus		OECD 201		
	Algae toxicity	NOEC mg/l	6,25	3 d					

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
25513-64-8	2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine			
		7 %	28	

12.3. Bioaccumulative potential

The product has not been tested.



Revision date: 11.12.2020

Safety Data Sheet

according to Regulation (EC) No 1907/2006

PES-III, Comp. B Page 9 of 12

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
25513-64-8	2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	-0,3
1477-55-0	m-Phenylenebis(methylamine)	0,18
90-72-2	2,4,6-Tris(dimethylaminomethyl)phenol	0,219
104-15-4	p-Toluenesulphonic acid	0,93

BCF

CAS No	Chemical name	BCF	Species	Source
1477-55-0	m-Phenylenebis(methylamine)	2,69		

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Subsequent waste code numbers of the European Waste Catalogue are considered as recommendations. Dispose of waste according to applicable legislation. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

List of Wastes Code - residues/unused products

080409

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - used product

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF 080409

> COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances;

hazardous waste

List of Wastes Code - contaminated packaging

WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND 150110 PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by

hazardous substances; hazardous waste

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 3259

AMINES, SOLID, CORROSIVE, N.O.S. (2,2,4(or 14.2. UN proper shipping name:

2,4,4)-trimethylhexane-1,6-diamine; m-Phenylenebis(methylamine))

14.3. Transport hazard class(es): 8



according to Regulation (EC) No 1907/2006

PES-III, Comp. B

Revision date: 11.12.2020 Page 10 of 12

14.4. Packing group:

Hazard label: 8

Classification code:
Special Provisions:
274
Limited quantity:
1 kg
Excepted quantity:
E2
Transport category:
4 Hazard No:
5 Tunnel restriction code:
5 E

Inland waterways transport (ADN)

14.1. UN number: UN 3259

14.2. UN proper shipping name: AMINES, SOLID, CORROSIVE, N.O.S. (2,2,4(or

2,4,4)-trimethylhexane-1,6-diamine; m-Phenylenebis(methylamine))

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8



Classification code: C8
Special Provisions: 274
Limited quantity: 1 kg
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number: UN 3259

14.2. UN proper shipping name: AMINES, SOLID, CORROSIVE, N.O.S. (2,2,4(or

2,4,4)-trimethylhexane-1,6-diamine; m-Phenylenebis(methylamine))

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8



Special Provisions: 274
Limited quantity: 1 kg
Excepted quantity: E2
EmS: F-A, S-B

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 3259

14.2. UN proper shipping name: AMINES, SOLID, CORROSIVE, N.O.S. (2,2,4(or

2,4,4)-trimethylhexane-1,6-diamine; m-Phenylenebis(methylamine))

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8



according to Regulation (EC) No 1907/2006

PES-III, Comp. B

Revision date: 11.12.2020 Page 11 of 12



Special Provisions:

Limited quantity Passenger:

Passenger LQ:

Excepted quantity:

A3 A803

5 kg

Y844

Excepted quantity:

E2

IATA-packing instructions - Passenger: 859
IATA-max. quantity - Passenger: 15 kg
IATA-packing instructions - Cargo: 863
IATA-max. quantity - Cargo: 50 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3: 2,4,6-Tris(dimethylaminomethyl)phenol

Information according to 2012/18/EU Not subject to 2012/18/EU (SEVESO III)

(SEVESO III):

Additional information

VOC content: 21,7 % (DIN EN ISO 11890-2)

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADN: Accord européen relativ au transport international des marchandises Dangereuses par voie de Navigation

(European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)

ADR: Accord européen sur le transport des marchandises dangereuses par route (Éuropean Agreement concerning the International Carriage of Dangerous Goods by Road)

BCF: Bioconcentration factor

CAS: Chemical Abstracts Service

CLP: Classification, Labeling and Packaging

DMEL: Derived Minimal Effect level DNEL: Derived No Effect Level



according to Regulation (EC) No 1907/2006

PES-III, Comp. B

Revision date: 11.12.2020 Page 12 of 12

EC50: Effective concentration, 50%

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations (DRG) for the air transport (IATA)

ICAO: International Civil Aviation Organization

IC50: Inhibitory concentration, 50%

IMDG: International Maritime Code for Dangerous Goods

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

NOEC: No Observed Effect Concentration

OECD: Oragnisation for Economic Co-operation and Development

PBT: persistent, bioaccumulative and toxic vPvB: very persistent and very bioaccumulative PNEC: Predicted No Effect Concentration

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

RID: Règlement concernant le transport international ferroviaire de marchandises dangereuses (Regulations

Concerning the International Carriage of Dangerous Goods by Rail)

VOC: Volatile organic compound Acute Tox. 4: Acute toxicity, Category 4

Aquatic Chronic 3: Long-term aquatic hazard, Category 3 Eye Dam. 1: Serious eye damage/eye irritation, Category 1 Eye Irrit. 2: Serious eye damage/eye irritation, Category 2 Skin Corr. 1B: Skin corrosion/irritation, Category 1B Skin Irrit. 2: Serious eye damage/eye irritation, Category 2

Skin Sens. 1: Skin sensitilization, Category 1

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Acute Tox. 4; H302	Calculation method
Skin Corr. 1; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)